



**Product Data Sheet**

**ATF DX III**

**Product Description:**

ATF DX III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger car, light vans and commercial vehicles.

ATF DX III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF DX III exceeds the following performance criteria.:

DEXRON IIF/G/H  
MAN 339 V1/V2  
Voith 55.6336  
ZF 11A/11B/14B/16L

Allison C4  
MB 236.10/236.9/236.7/236.5/236.1  
Volvo 97341

CAT TO-2  
Voith 55.6335  
Mercon

MAN 339 Z1/Z2  
ZF 02F/03D/04D

Properties	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m3	ASTM D4052	855
Kin. Viscosity @40°C	mm2/s	ASTM D7042	35
Kin. Viscosity @100°C	mm2/s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	210
Viscosity Brookfield @-40°, max.	cP	ASTM D5293	17500
Flash Point COC	°C	ASTM D92	201

Product Nr: 4322

Date Issued: 17/01/2016

Date Superseded: 31/05/2012

Revision nr: 03