



Product Data Sheet:

AUTOGEAR OIL MP 85W-140

Product Description:

AUTOGEAR OIL MP 85W-140 is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives where an API GL-5 oil is specified.

AUTOGEAR OIL MP 85W-140 is formulated from carefully selected base stocks and well balanced extreme pressure additives. **AUTOGEAR OIL MP 85W-140** gives excellent protection towards gear components regarding wear and scoring. Furthermore **AUTOGEAR OIL MP 85W-140** provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

AUTOGEAR OIL MP 85W-140 exceeds the specifications of API GL-5 and MIL-L-2105D, as well as the requirements of most “Original Equipment Manufacturers” (OEMs).

AUTOGEAR OIL MP 85W-140 is recommended for certain manual transmissions and final drives requiring oils meeting API GL-5 in on road passenger cars, light- and heavy duty trucks, buses and vans and is also recommended for off highway equipment, in construction, mining and agriculture.

Specifications:

Exceeds: API GL-5, US Army MIL-L-2105D

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J306	85W-140
Density @ 15°C	ASTM D4052	910 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	421 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	29.1 mm ² /s
Low-Temperature Brookfield Viscosity @ -12°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	96
Flash Point	ASTM D92	210°C
Pour Point	ASTM D97	-15°C

Product nr: 4308

Date Issued: 08/08/2011

Date Superseded: 08/07/2010

Revision nr: 01