



A brand of **TOTAL**

ELF EVOLUTION 500 FTX 10W-30



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines



APPLICATIONS

Most recent technology engines

- Premium multi-grade motor oil for all engines, recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SN; ILSAC GF-5

CUSTOMER BENEFITS

Fuel Economy

- Promoted fuel saving

Excellent engine protection

- Excellent start-up performance, prevents sludge build-up and controls oxidation

Optimum performance

- Optimum power and performance under most severe driving conditions

Low emission vehicle

- Fully compatible with all emission control devices

CHARACTERISTICS

	Method	Units	SAE Grade 10W-30
Density at 15°C	ASTM D1298	Kg/m ³	868
Viscosity at 40°C	ASTM D445	mm ² /s	67
Viscosity at 100°C	ASTM 445	mm ² /s	10
Viscosity index	ASTM D2270	-	128
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	234

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 500 FTX 10W-30

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.