

## AC-82 Diesel Biocide

### Description

AC-82 Diesel Biocide is intended where distillate fuels are used such as bulk storage tanks, diesel trucks, marine diesel engines, farm equipment and diesel generators. Where water is present in a storage tank it will provide a location for algae and bacteria to grow in a layer between the water and fuel. Once the population of the microbe or fungus reaches a certain size dieback occurs and then filters can become blocked with a black slimy deposit and the fuel may be hazy with water and dirt. This can reduce the performance.

### Features & Benefits

AC-82 is excellent for use with all forms of diesel and bio diesel.

AC-82 has been formulated to treat more types of algae and bacteria than other brands

AC-82 is a concentrated formula for treatment of more litres per millilitre added.

AC-82 promotes fuel stability during storage..

### Directions for Use

Maintenance Dose: 1 Litre / 2,000 Litres of Diesel

Contamination Dose: 1 Litre / 1,000 Litres of Diesel

### Typical Properties

<b>Appearance:</b>	Clear to yellow liquid	<b>Boiling Point</b>	100 - 110°C
<b>Odour:</b>	Slight Odour	<b>Solubility</b>	Soluble in water
<b>pH</b>	12	<b>ADG Code</b>	Not a Dangerous Good
<b>Flammable:</b>	C1 Combustible Liquid	<b>Spec. Gravity</b>	1.0 - 1.2